



JST20E-1200BW 20A TRIAC

Rev.A.1.1

DESCRIPTION:

20E 1200BW

AC

1200V

20A

20E

20E 1200BW

1200V

20A

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage Temperature	T_{stg}	-40-150	
Junction Temperature	T_j	-40-125	
Reverse Voltage (T _j = 25℃)	V_{RRM}	1200	V
Forward Voltage (T _j = 25℃)	V_{FM}	1200	V
Non-Repetitive Forward Current (T _j = 25℃, t _{on} ≤ 100μs)	I_{FSM}	20	A
Forward Current (T _j = 25℃)	I_{FT}		

JST20E-1200BW



JieJie Microelectronics Co., Ltd.

物

(T=25 ; 0 -10 -15 8)

V_p

3.8

W

JST20E-1200BW (-)4 (0.0091 T1 15.960.274 0w 5.0415.965.041198.12.


FIG.7: 



品名: 贴片

规格:

-61000-4-5 封装



ORDERING INFORMATION

Order code	Voltage $V_{\text{DRM}}/V_{\text{RRM}}$ (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		- -			
JST20E-1200BW	1200	50	TO-263	50	Tube
JST20E-1200BW-TR				800	Tape & Reel

Document Revision History

Rev	Rev	Rev
A. 1.2, 2023	A. 1.0	1.0
C. 20, 2025	A. 1.1	Revised

DELIVERY MODE



