



JST24C-800C 25A TRIAC

Rev.A.1.1

DESCRIPTION:

ELECTRICAL CHARACTERISTICS (T_j=25 unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I _{GT}	V _D =12V R _L =33Ω	- -	MAX.	25	mA
				50	
V _{GT}	V _D =V _{DRM} T _j =125 R _L =30.3Ω	ALL	MAX.	1	V
V _{GD}					

ORDERING INFORMATION

J	ST	24	C	-800	C
JieJie Microelectronics Co., Ltd.	Triacs	$I_{T(RMS)}:25A$			$C:I_{GT1-3} \ 25mA \ I_{GT4} \ 50mA$
		C:TO-220C		$800:V_{DRM} / V_{RRM} \ 800V$	

MARKING



	XXX XXX Year _____ Month _____ Production Code
---	---

FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards AC



INPUTFiltering U

Order code	Voltage $V_{\text{DRM}}/V_{\text{RRM}}$ (V)	IGT(mA)	Package	Base qty. (pcs)	Deliver.

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document are for reference only. The actual products and information may vary without notice.